





Intelligent Blocker

ICE 900

Optional accessories Barcode scanner, USB flash drive

Dimensions / Weight
Standard accessories

Spare fuse, Interface cable, Stylus pen, Power cord,

Table for shape imager, Small diameter lens holder

256 (W) × 367 (D) × 352 (H) mm / 8 kg

 $10.1 (W) \times 14.4 (D) \times 13.9 (H) " / 17.6 lbs.$ 

Power supply

ower consumption

50 VA

AC 100 to 230 V / 230 V 50 / 60 Hz

4 PS-232C, 1 LAN ( 10 / 100 Base-T )

8.4-inch SVGA color LCD touch panel

nterface

Blocking method

Motor drive





# Comfort is the highest priority

operations are possible with a combination of the Twin Jog Dial able to provide comfortable and swift operation than ever before. Most Addition to the intuitive operation of touch screen, Twin Jog Dial is avail-


## New graphic design

derstood easily by the Information bar Reforming graphic design, and movies. been achieved. Operation can be unuser-friendly and smart screen has

### Data management

GHIER PARTY

saved. Data can also be saved to USB flash drive (optional). Maximum30, 000 patterns can be quick search of a needed job data. design and the Twin Jog Dial provide a The combination of new graphic



# Data

the highest blocking precision. blocking surface horizontally yielding the lens stage, it always maintains the By applying upper surface reference to

### Motor drive block

is located at the most comfortable position. Ice 900 is equipped a motorized blocking. Cup holder Accessory tray

### Tiltable display


Nidek's edger, Lex 1000 and Le 1000 angle of the display at the lowest posient angles depending on uses. The tion is equivalent to those ones of The display can be tilted at four differ-

# Integrated shape imager

automatically. detects holes and horizontal axis tern or a demo lens, but now it also Not only detecting a shape of a pat-

ME-1000 + Lt 910 + Ice 900

NIDEK CO., LTD.





of Nidek's trademarks. Unexcepof lens edgers and blockers is one Edgers. nected with current Nidek Lens tionally, Ice 900 can be con-Customable system configuration

also connectable. 'LE-9000 and LE-9000Express are

